

Product Information: ER1000

Compact Loaders



ER1000 is a mini telescopic loader with a 3500mm lifting height. This machine is perfectly suited for various types of projects, including use in small spaces as it has a width of 1.26 m.

The ER1000 IS extremely reliable and equipped with a ROPS/FOPS-approved safety roof.



MODEL: EVERUN- ER1000

- **KUBOTA1105 EURO5/EPA4 ENGINE, ITALY HYDROSTATIC**
- **DRIVING SYSTEM, INCHING FUNCTION, QUICK HITCH**
- **26*12-12 GRASS TIRES**
- **ADJUSTABLE STEERING WHEEL & SEAT**
- **ELECTRICAL JOYSTICK with FLOATING FUNCTION**
- **PRESSURE CHECKING SYSTEM**
- **ENCLOSED CABIN -OPTIONAL**
- **LED WORKING LIGHT**
- **BOBCAT QUICK HITCH**
- **EVERUN ARTICULATING PIN SHAFT**

Nationwide Distribution From

Los Angeles Location

27788 Hancock Parkway
Valencia, CA 91355

Chicago Location

257 Commonwealth Dr.
Carol Stream, IL 60188



Product Information: ER1000

Technical Parameter

Rated Load	900kg	Overall width	1260mm
Bucket Capacity	0.3m3	Overall Height	2310mm
Lifting Height of main boom	2959mm	Wheel base	1507mm
Dumping Height of main boom (dumping angle 45°)	2051mm	Tread	890mm
Dumping reach of main boom	587mm	Min. Ground clearance	220mm
Max. Loading capacity of main boom	1000kg	Net weight	2100kg
Lifting height of small boom	3526mm	Engine model	Yanmar 3TNV88F-ESSY
Dumping height of small boom (dumping angle 45°)	2618mm	Rated Power	19.2kw
Dumping reach of small boom	1085mm	Rated Speed	2200r/min
Max. Loding capacity of small boom	600kg	Max. Torque	98.7N.m
Max. Speed(F1/R1)	12km/h	Speed at Max. Torque	1320r/min
Max. Breakout Force	15KN	Bore & stroke	88*90
Digging Deep	65mm	Rated fuel consumption	≤230
Max. Gradeability	25°	Driving	4 wheel drive
Max. Turning angle	35°	Tire	26*12-12
Overall length (bucket on ground position)	3820mm	Oil flow	13.8ml/r
		Working pressure	16Mpa



EVERUN[®]
America

Nationwide Distribution From

Los Angeles Location

27788 Hancock Parkway
Valencia, CA 91355

Chicago Location

257 Commonwealth Dr.
Carol Stream, IL 60188

